

# METAPACE

# T-1



**5 years  
warranty**

## Specifications

<b>Printing Method</b>	Direct Thermal
<b>Equipment</b>	Autocutter, two connections for cash drawers, Paper Near End /End Sensor
<b>Colour</b>	Black or White
<b>Printing Speed</b>	150 mm/s
<b>Roll Changes</b>	Easy Paper Drop-In (single-handed and without contriving)
<b>Resolution</b>	7 Dot/mm (180 dpi)
<b>Character Set</b>	Alphanumeric: 96 characters
<b>Extended Graphic</b>	128 x 7 pages (1 space page)
<b>Character Size</b>	Size: Font A: 12 x 24, Font B: 9 x 17; per line: Font A: 42, Font B: 56
<b>Consumables</b>	Thermal paper
<b>Paper</b>	Width: max. 83 mm, core: max. 19 mm
<b>Durability</b>	100 km TPH (direct thermal printhead), 1,5 million cuts (Autocutter)
<b>Flash Memory</b>	16 Mbit
<b>Memory for logos</b>	256 KB (NV RAM)
<b>Barcodes</b>	EAN-13, EAN-8, Code 39, Code 93, Code 128, ITF, Coda bar, UPC-A, UPC-E
<b>Emulation</b>	ESC/POS
<b>Driver</b>	Windows 95/98/Me/2000/NT/XP/2003 Server, OPOS
<b>Sensors</b>	Paper end, paper near end, wall mounting near end, cover open
<b>Memory</b>	8 KB printer buffer, 256 KB memory for logos (NV RAM)
<b>Interfaces</b>	RS232C, parallel, USB; Ethernet, DUAL (serial/USB) optional
<b>Options</b>	Wallmount
<b>Power supply</b>	AC120V-230V +/- 10 %, DC24V, 2,3A
<b>Dimensions (mm)</b>	145 (W) x 195 (L) x 146 (H)
<b>Warranty</b>	60 months