





Model	P330i	P430i	P110i	P120i
				
Card Volume	Medium to High	Medium to High	Medium	Medium
Security Level	Medium to High	Medium to High	Medium	Medium
Print Parameters				
Print Color	Full Color Monochrome	Full Color Monochrome	Full Color Monochrome	Full Color Monochrome
Card Printing	Single-sided	Dual-sided	Single-sided	Dual-sided
Print Speed	144 cards/hr single-sided (YMCKO)	102 cards/hr dual- sided (YMCKOK) 130 cards/hr single-sided (YMCKO)	30 seconds/card single-sided (YMCKO)	40 seconds/card dual-sided (YMCKOK) 30 seconds/card single-sided (YMCKO)
Resolution	300 dpi	300 dpi	300 dpi	300 dpi
Lamination	No	No	No	No
Media Capability				
Card Thickness	10 mil (.25mm) to 60 mil (1.524mm)	10 mil (.25mm) to 60 mil (1.524mm)	30 mil (.76mm)	30 mil (.76mm)
Card Types	CR-80 PVC & Composite	CR-80 PVC & Composite	CR-80 PVC & Composite	CR-80 PVC & Composite
Input Feeder	100 cards (30 mil) Optional 220 cards feeder	100 cards (30 mil) Optional 220 cards feeder	100 cards (30 mil)	100 cards (30 mil)
Output Hopper	100 cards (30 mil)	100 cards (30 mil)	45 cards (30 mil)	45 cards (30 mil)
Connectivity				
Interface	USB 1.1 (USB 2.0 Compatible) Optional Built-in 10/100 Ethernet	USB 1.1 (USB 2.0 Compatible) Optional Built-in 10/100 Ethernet	USB 1.1 (USB 2.0 Compatible)	USB 1.1 (USB 2.0 Compatible)
Drivers	Windows® 2000 and XP	Windows® 2000 and XP	Windows® 2000 and XP	Windows® 2000 and XP
Encoding Options				
3 track magnetic stripe encoder (HiCo/LoCo)	Yes	Yes	Yes	Yes
Smart card contact station	Yes	Yes	No	No
Smart card contact encoder (ISO 7816)	Yes	Yes	No	No
Smart card contactless encoder (MIFARE®/DESFire)	Yes	Yes	No	No
Smart card contactless encoder (HID iClass®)	Yes	Yes	No	No

Physical				
Size (H W D)	10.1" x 18.2" x 9.4" (256 x 462 x 239 mm)	10.1" x 26" x 9.4" (256 x 660 x 239 mm)	8.5" x 7.9" x 12.9" (216 x 201 x 328mm)	8.5" x 7.9" x 12.9" (216 x 201 x 328mm)
Weight	15.5 lbs (7.0 kg)	20 lbs (9.1kg)	9.5 lbs (4.3 kg)	9.5 lbs (4.3 kg)